



## 2 CHARACTERISTICS

Screed for finishing superficially the floors. This equipment main characteristic is its low weight, one person can use it alone. The use of rail-guide is not necessary, this machine is suitable for working directly on the concrete mass. The aluminium beam presents a high resistance and a good finishing. On the screeds with petrol engine, vibration can be controlled with the accelerator.

### ENGINES CHARACTERISTICS

PETROL ENGINES:

Model	<b>HONDA GX-25 TORNADO GH QZGH QXH</b>	<b>ROBIN EH 025 TORNADO GR4T QZ GR4T QX R4T</b>	<b>HONDA GX-35 HURACAN GH</b>	<b>ROBIN EH035V HURACAN GR</b>
<b>Type/Displacement</b>	4 stroke / 25cc	4 stroke / 24,5 cc	4 stroke / 35,8 cc	4 stroke / 33,5cc
<b>Max output/R.P.M.</b>	1,1 HP / 7000 r.p.m.	1,1 HP / 7000 r.p.m.	1,6 HP / 7000 r.p.m.	1,6 HP / 7000 r.p.m.
<b>Carburettor</b>	Diaphragm type	Diaphragm type	Diaphragm type	Diaphragm type
<b>Ignition</b>	Transistors magneto	Transistors magneto	Transistors magneto	Transistors magneto
<b>Starting</b>	Coil	Coil	Coil	Coil
<b>Fuel</b>	Petrol	Petrol	Petrol	Petrol
<b>Fuel tank capacity</b>	550 cc	500 cc	700 cc	750 cc
<b>Weight</b>	2,78 kg	2,8 kg	3,33 kg (without clutch)	3,4kg

ELECTRIC MOTOR:

<b>Type</b>	Single phase electric motor
<b>Power</b>	105W
<b>Max R.P.M.</b>	2850
<b>Condensator</b>	5 $\mu$ F / 400 V (QXE), 10 $\mu$ F / 400 V (QZE)
<b>Voltage</b>	220V 50Hz
<b>Weight</b>	4 kg

### VIBRATING SCREEDS CHARACTERISTICS:

Model>	<b>TORNADO G</b>	<b>TORNADO E</b>	<b>QXG</b>	<b>QXE</b>	<b>QZG</b>	<b>QZE</b>	<b>HURACAN GH</b>	<b>HURACAN GR</b>
<b>Beam length (m)</b>	1,5-3	1,5-3	1,5-3	1,5-3	2-3	2-3	2-5	2-5
<b>Weight (kg)</b>	15,5-20	14,5-19	13,5-18	12,5-17	17-22	17,5-22,5	22,9-35,5	22,9-35,5
<b>Centrifuge force (kp)</b>	150	70	150	70	150	70	200	200