



5.2 Hilti TE 905 breaker



Hilti TE 905 breaker




Technical data

| | | | | | |
|---|---|--------|--------|--------|---------------|
| Power input: | 1550 W | 1550 W | 1600 W | 1600 W | 1600 W |
| Voltage (versions): | 100 V | 110 V | 115 V | 220 V | 230 V / 240 V |
| Current input: | 15 A | 16 A | 15 A | 8,2 A | 8,3 A / 8,3 A |
| Frequency: | 50-60 Hz | | | | |
| Machine weight: | 11.3 kg | | | | |
| Dimensions: | 680x110x180 mm | | | | |
| Hammering speed under load: | 2200 blows/min. | | | | |
| Single impact energy: | 20 Joules | | | | |
| Chiselling performance in medium-hard concrete: | 1300 cm ³ | | | | |
| Chisels: | Pointed, flat, wide flat, asphalt and flexible chisels Bushing, tamping and ground-rod ramming tools | | | | |
| Chuck: | TE-S | | | | |
| Permanent lubrication | | | | | |
| Adjustable side handle | | | | | |
| Foam-rubber padded grip and side handle | | | | | |
| Automatic cut-out carbon brushes | | | | | |
| Electronic speed (r.p.m.) limitation | | | | | |
| On/off switch | | | | | |
| Vibration reduction with built-in AVR system | | | | | |
| Service indicator LED | | | | | |
| Protection class II (double insulated) | | | | | |
| Radio and TV interference suppression | | | | | |
| The noise level of the machine is less than 108 dB (A) | | | | | |
| Wear ear protection. | | | | | |
| The typical weighted vibrational acceleration is 8 m/s ² . | | | | | |
| Right of technical modifications reserved | | | | | |

Kit supplied with the machine


Plastic toolbox, cleaning cloth, Hilti insert tool grease and operating instructions



EC declaration of conformity

Designation: Breaker
 Serial numbers: XX.0000001-9999999/XX
 Model/type: TE 905
 Year of design: 1996
 We declare under our sole responsibility that this product is in conformity with the following standards or standardisation documents:
 EN 50144, EN 55014 or EN 55011,
 EN 60555 according to the provisions of the directives 73/23/EEC, 89/336/EEC, 89/392/EEC, 84/537/EEC.

Hilti Corporation


 Dr. Heinrich Schlippe
 Vize-Präsident D&ET Division
 11/1996

Do not use this product in any way other than as directed by these operating instructions.

Observe the national regulations applicable to the operation of this machine.

The operating instructions should always be kept with the machine!